

NEW CONC. WALKWAY

5'-6"

8'-0"

9'-0"

8'-6"

8'-6"

WATER P.O.C.

HB

NO PARKING

NEW 6' CONC. CURB

4'-0"

4'-0"

4'-2"

18'-0"

1'-0" MAX.

1'-0" MAX.

WHEEL STOP, TYP.

NEW DISABLED ACCESSIBLE SIGN, SEE DET. 4/105.0

GROOVING: 1/4" D GOOVES, 3/4" O.C.

NEW CONC. WALKWAY, 2% MAX. SLOPE

FLARED SIDES 1:10 MAX. SLOPE

48' x 48' LANDING

HB WATER CUT-OFF

HB WATER CUT-OFF

EXISTING CONC. WALKWAY TO STREET

****RAMP PER CBC 11B-406.5

24

18'-0"

36" TYP.

2'-0"

3'-0"

5'-0"

9'-0"

8'-11"

8'-11"

'NO PARKING', TYP.
SEE DET. 1/ID5.0

4' WIDE BLUE STRIPE

NO PARKING

NEW INTERNATIONAL SYMBOL PAINTED ON ASPHALT, TYP.
SEE DET. 6/ID5.0

WHEEL STOP, TYP.

NEW DISABLED ACCESSIBLE SIGN, SEE DET. 4/ID5.0

EXISTING 6' CURB TO REMAIN

EXISTING IRRIGATION CONTROLS

NEW DISABLED ACCESSIBLE SIGN, SEE DET. 5/ID5.0

FIRE HYDRANT

EXISTING DRIVEWAY

1/2" D. PIFERAIL.
SEE DET. 3/A5.0

NEW CONC. PAD &
STEP. SEE DET.
3/A5.0

24"

7'-6"

12"

12"

24"

6"

5'-0"

STEP
DOWN

EXIT
DOOR

PLAN VIEW 1/4"=1'-0"

1/2" SQ.. MTL. PIPE
HANDRAIL. POWDER
COAT FINISH (BROWN)
TO MATCH EXISTING

1/2" SQ.. MTL. PIPE RAIL.
OPENING BETWEEN
RAILS TO BE 4" MAX.
CLR. PAINTED (BROWN)
TO MATCH EXISTING

12"

34" TO 38"

12"

34" TO 38"

34" TO 38"

12"

24"

PLUS TREAD
WIDTH, MIN.

WARNING STRIPE OF
CONTRASTING COLOR.
(EXTERIOR STAIRS.
ALL TREADS TO HAVE
WARNING STRIPES)

REINFORCE
CONC. STAIRS
AND WALKWAY

TYP. SECTION 1/2"=1'-0"

NOTE:
SIGN TO BE CENTERED IN FRONT OF EACH H.C. PARKING STALL WITHIN CLEAR VIEW BUT NOT TO OBSTRUCT PASSAGE FROM PARKING STALL OR ANY SIDEWALK.

DISABLED ACCESSIBLE PARKING SIGNAGE - AT STALL

4 DISABLED ACCESSIBLE SIGNAGE

TO BE MOUNTED AT PARKING LOT ENTRANCES

DISABLED ACCESSIBLE PARKING SIGNAGE - SITE ENTRANCE

5

DISABLED ACCESSIBLE PARKING SIGNAGE - SYMBOL IN STALL

6

DISABLED ACCESSIBLE PARKING SIGNAGE - AT OFF-LOADING AREA

7

DETECTABLE WARNINGS

8

NTS

DATE:	02/18/2014
DRAWN BY: FGS	
SCALE:	A5-NOTED
JOB NO:	7818WC
DRAWING NAME:	WC-DET-A5.0
SHEET NO:	